



Technical Specification

Modal No.	OD-MPPT-SCC-12/24-75/25
Technology	MPPT
Product Series	OD-MPPT-SCC
Battery Operating Mode	12V/ 24V
SPV (Pmax)	400W (12V Battery)/ 800W (24V Battery)
Solar Input Voltage (Voc max)	75Voc (Open Circuit Voltage)
Solar Input Voltage (Voc min)	18V (for 12V Battery), 36V (for 24V Battery)
Charging Method	MCCV Mode
Battery Type	Lead- Acid (Tubular/SMF)
Self-Power Consumption	<2W
Maximum Charging Current	25A
Display	16x2 Character Display (Continuous Working)
Parameters Displayed on LCD	Solar Voltage (Vsol), Solar Current (Isol), Solar Power (Sol PWR) Battery Voltage (Vbat), Charging Current (Ichg), Solar Panel Generated Unit
Indications	Solar Reverse, Battery Reverse/Fuse Blown LED
Switch	Power ON/ OFF
Solar Reverse Current Protection	Yes
Battery Reverse Protection	Yes(1 Fuse)
Fuse Protection	Yes (Externally Accessible)
Spare Fuse Provided	Yes
Switching Element	MOSFET
Efficiency	Up to 95%
Cooling	Fan (Forced Air Cooling) with adaptive Controlling for Longer Life. Fan turns on once the Charging Current goes above 6A and turns off when it goes below 4A.
Connection	Bakelite Screw Terminal
Enclosure Type	MS (Ivory Color)
Mounting Type	Retrofit Wall Mounted
Temperature	0°C TO 50°C
Product Dimensions (L*W*H)	18 *16 *10 CM
Packaging Dimensions (L*W*H)	22*22*14 CM
Weight	1.540Kg